

Aqua Flexo Label Series Inks

PRODUCT DESCRIPTION

This series of aqueous flexographic inks are formulated to provide high performance adhesion, flexibility, gloss and rub resistance on label paper and film, including PE, PP and PVC. These inks give maximum color strength for modern presses equipped with higher line count, lower bcm (I.e. 1000 lines – 1.0 bcm) anilox rollers. All colors are low in V.O.C. and offer excellent press stability with little or no adjustment needed during a press run. It is recommended that the user pretest before use to verify compatibility with all substrates, inks and coatings.

SUBSTRATES AND APPLICATIONS

- Paper
- PE Films
- PP Films
- PVC Films

CHARACTERISTICS

- Excellent Color Strength
- Fast Drying
- Flexible
- Gloss Finish
- High Mileage
- Press Speeds up to 400 feet per minute
- Excellent Press Stability
- Superior Rub Resistance
- Compatible with Aqueous or UV Overprint Clears
- Low V.O.C., Ammonia Free

PROCESS COLORS

F-17840	Process Yellow	F-17841	Process Magenta
F-17842	Process Cyan	F-17843	Process Black
F-19252	Process Yellow LF	F-19253	Process Magenta LF

STANDARD COLORS

F-19254	Opaque White	F-19256	Extender
F-19300	Retarder		

Custom Colors are available upon request.

STORAGE

Protect from freezing. Store at room temperature (Below 100 F.) Reseal containers tightly.

PACKAGING

Sold by the pound. Available in gallon and 5 gallon containers.

PRECAUTIONS

Read the Material Safety Data Sheet prior to processing. It contains instructions for precautions when processing, handling and storing inks, and important first aid information.

Technical
Data

OBLIGATION OF MANUFACTURER/SELLER

The following is made in lieu of all warranties, expressed or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct, or incidental or consequential, arising out of the use of or the inability to use the product. Before using, the user shall determine the suitability of the product for his intended use and user assumes all risk and liability whatsoever in connection therewith. The foregoing may not be altered except by an agreement signed by officers of seller and manufacturer. ALWAYS PRE-TEST BEFORE RUNNING PRODUCTION.