Euro-Tech

PRODUCT DESCRIPTION

This ink is a sheetfed offset lithographic ink designed for printing on non-porous substrates including acetate, polyester, polystyrene, PVC, and treated polyolifins (Tyvek®, Yupo®). It is an environmentally friendly, low V.O.C., fast drying ink, with very high gloss and a hard dry surface. The rheology and tack are adjusted to give excellent dot and fine line reproduction with excellent press stability. Euro-Tech inks meet all Federal, State, and local government and Industry standards for air quality, health and safety.

SUBSTRATES AND APPLICATIONS

- Acetate
- Treated Polvester
- Polystryrene
- PVC
- Treated Polyolifins

CHARACTERISTICS

- Dries to a hard surface
- Flexible
- High Gloss
- Low V.O.C.

COLOR RANGE

M-38050	Yellow	M-38051	012 Yellow
M-38052	021 Orange	M-38053	Warm Red
M-38054	032 Red	M-38055	Rubine Red
M-38056	Rhodamine Red	M-38057	Purple
M-38058	Violet	M-38059	072 Blue
M-38060	Reflex Blue	M-38061	Process Blue
M-38062	Green	M-38063	Black
M-38064	Tinting White	M-38065	Opaque White
M-38066	Process Cyan	M-38067	Process Magenta
M-38068	Process Yellow	M-38069	Process Black

USE As with any ink, it is recommended that the ink be pretested for suitability to

substrate and pressroom conditions before running production.

STORAGE Protect from freezing. Store at room temperature (Below 100 F.) Reseal

containers tightly.


PACKAGING Available in 1 lb, 5.5 Lb, 20 Lb, 30 Lb and 45 Gallon kits.

PRECAUTIONSRead the Material Safety Data Sheet prior to processing. It contains instructions

for precautions when processing, handling and storing inks, and important first aid

information.

Technical Data



The following is made in lieu of all warranties, expressed or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct, or incidental or consequential, arising out of the use of or the inability to use the product. Before using, the user shall determine the suitability of the product for his intended use and user assumes all risk and liability whatsoever in connection therewith. The foregoing may not be altered except by an agreement signed by officers of seller and manufacturer. ALWAYS PRE-TEST BEFORE RUNNING PRODUCTION.

